



**HP**



# DS508

## FEATURES

- **HANDLING:**  
Two columns of longitudinal blocks ensure straight driving stability. Wide tire shoulder blocks supply accurate handling response.
- **GRASP:**  
Masses of grooves on tire shoulder enhance even grasp.
- **STEERING:**  
Optimized tire shoulder pattern design improves heat radiation and steering performance.

**Suitable for mini van. Rib and lug pattern groove designed to suit for a variety of roads.**

| Tire Size   | Loading Index | Speed Rating | Load Range | Tread Depth (mm) | Section Width (mm) | Overall Diameter (mm) | Std. Rim | Max. Load (Kg) | Std. Cold Infl. Press (KPa) | UTQG    |
|-------------|---------------|--------------|------------|------------------|--------------------|-----------------------|----------|----------------|-----------------------------|---------|
| 165/70R13   | 79            | T            | SL         | 7.0              | 170                | 562                   | 5.00B    | 437            | 250                         | 420/A/A |
| 165/70R13   | 83            | S            | XL         | 7.0              | 170                | 562                   | 5.00B    | 487            | 290                         | 420/A/A |
| 165/70R13C  | 88/86         | S            | 6PR/C      | 6.5              | 170                | 562                   | 5.00B    | 560/530        | 375                         | 420/A/A |
| 165/70R13LT | 88/86         | S            | 6PR/C      | 6.5              | 170                | 562                   | 5.00B    | 560/530        | 375                         | 420/A/A |
| 165/70R13LT | 94/92         | S            | 8PR/C      | 7.5              | 170                | 562                   | 5.00B    | 775/730        | 450                         | 420/A/A |
| 165/70R13LT | 94/92         | R            | 8PR/C      | 7.5              | 170                | 562                   | 5.00B    | 775/730        | 450                         | 420/A/A |
| 175/60R13   | 84            | H            | XL         | 7.5              | 177                | 544                   | 5.00B    | 500            | 290                         | 420/A/A |
| 175/70R13   | 82            | T            | SL         | 7.5              | 177                | 576                   | 5.00B    | 475            | 250                         | 420/A/A |
| 185/70R14   | 88            | H            | SL         | 8.0              | 189                | 616                   | 5.5J     | 560            | 250                         | 420/A/A |
| 205/70R14   | 98            | T            | XL         | 9                | 209                | 644                   | 6J       | 750            | 290                         | 420/A/A |
| 205/70R14C  | 102/100       | T            | 6PR/C      | 9                | 209                | 644                   | 6J       | 850/800        | 375                         | 420/A/A |