



DOUBLESTAR

Doublestar Tire · Innovating the World

LONG HAUL

DSR/HR168



FEATURES

- COMFORT:**
 Combination of longitudinal and transverse grooves supply excellent traction, steering, braking and wet resistance, ensures safe and comfortable driving.
- ECONOMY:**
 Optimized tread formula provide super wear & puncture resistance, ensure long mileage.

Suitable to all wheel position of truck, bus, trailer on a variety of road conditions.



Tire Size	Ply Rating	Tread Depth		Standard Rim	Load kg		Pressure kpa		Loading Index		Speed Rating	Inflated Diameter			
		mm	1/32in		single	dual	single	dual	single	dual		mm		inch	
												Overall Diameter	Section Width	Overall Diameter	Section Width
1100R20	18	15	19	8.00	3550	3250	930	930	152	149	K	1082	286	43	11
11R22.5	16	17	21	8.25	3150	2900	850	850	148	145	L	1054	279	41	11
11R24.5	16	17	21	8.25	3250	3000	830	830	149	146	M	1104	279	43	11
1200R20	18	16	20	8.50	3750	3450	830	830	154	151	K	1125	315	44	12
1200R24	20	12	15	8.50	4500	4125	900	900	160	157	L	1251	340	49	13
12R22.5	16	16	20	9.00	3350	3075	830	830	150	147	M	1084	300	43	12
13R22.5	18	17	21	9.75	3750	3350	850	850	154	150	K	1124	320	44	13
315/80R22.5	18	18	23	9.00	3750	3450	830	830	154	151	M	1076	312	42	12
900R20	16	16	20	7.00	2800	2650	900	900	144	142	K	1019	259	40	10
1000R20	16	16	20	7.50	3000	2630	840	770	146	143	K	1054	278	41	11