



DOUBLESTAR

Doublestar Tire · Innovating the World

LONG HAUL



DSR266/DSR266W



FEATURES

- HANDLING:**
 Excellent traction and guiding stability, low noise emission supply comfortable driving.
- DRAINAGE:**
 Longitudinal grooves provide excellent draining to ensure driving safety on wet ground.
- ECONOMY:**
 Low rolling resistance, excellent heat radiation, fuel efficiency. Excellent loading capacity, more original mileage.

Suitable to all wheel position of bus on road and expressway.



Tire Size	Ply Rating	Tread Depth		Standard Rim	Load kg		Pressure kpa		Loading Index		Speed Rating	Inflated Diameter:			
		mm	1/32in		single	dual	single	dual	single	dual		mm		inch	
												Overall Diameter	Section Width	Overall Diameter	Section Width
8.5R17.5	12	13	16	6.00	1450	1400	625	625	121	120	L	802	215	32	8
9R22.5	14	12	15	6.75	2240	2140	830	830	136	134	M	970	230	38	9
9.5R17.5	16	13	16	6.75	1850	1750	750	750	129	127	L	842	240	33	9
10R22.5	16	12	15	7.50	2800	2650	850	850	144	142	L	1020	254	40	10
11R24.5	16	14	18	8.25	3250	3000	830	830	149	146	M	1104	279	43	11
12R22.5	16	15	19	9.00	3350	3075	830	830	150	147	M	1084	300	43	12
12R22.5	18	15	19	9.00	3550	3250	930	930	152	149	M	1084	300	43	12
225/75R17.5	16	13	16	6.75	1850	1750	725	725	129	127	L	783	226	31	9
235/75R17.5	16	13	16	6.75	2000	1900	775	775	132	130	M	797	233	31	9
235/75R17.5	18	13	16	6.75	2725	2575	875	875	143	141	J	797	233	31	9
245/70R19.5	16	13	16	7.50	2240	2120	825	825	136	134	L	839	248	33	10
265/70R19.5	16	13	16	7.50	2500	2360	775	775	140	138	L	867	262	34	10
275/70R22.5	16	15	19	8.25	3150	2900	900	900	148	145	L	958	276	38	11
275/80R22.5	16	13	16	8.25	2900	2725	750	750	145	143	L	1012	276	40	11
285/75R24.5	16	14	19	8.25	3075	2800	830	830	147	144	M	1050	283	41	11
295/75R22.5	16	14	18	9.00	3000	2725	830	830	146	143	M	1014	298	40	12
295/80R22.5	18	15	19	9.00	3550	3150	850	850	152	148	L	1044	298	41	12
315/70R22.5	18	15	19	9.00	3750	3350	900	900	154	150	L	1014	312	40	12
315/80R22.5	18	15	19	9.00	3750	3450	830	830	154	151	M	1076	312	42	12
315/80R22.5	20	15	19	9.00	4000	3350	850	850	156	150	M	1076	312	42	12