

DOUBLESTAR

Doublestar Tire · Innovating the World

MINING OR OFF ROAD



DSR668



FEATURES

- **LOADING:**
Strengthened tire bead design improves tire intensity, supplies better overloading capacity.
- **SAFETY:**
Big block pattern provides outstanding cut and puncture resistance performance.

Suitable to all wheel position of overloading dump trucks on minery, mixed road and off-road field.



Tire Size	Ply Rating	Tread Depth		Standard Rim	Load kg		Pressure kpa		Loading Index		Speed Rating	Inflated Diameter			
		mm	1/32in		single	dual	single	dual	single	dual		mm		inch	
												Overall Diameter	Section Width	Overall Diameter	Section Width
11R22.5	16	25	31	8.25	3150	2900	850	850	148	145	J	1065	279	42	11
11R24.5	16	25	31	8.25	3250	3000	830	830	149	146	J	1116	279	44	11
12R22.5	16	25	31	9.00	3350	3075	830	830	150	147	M	1084	300	43	12
295/80R22.5	18	23	29	9.00	3550	3150	850	850	152	148	J	1050	298	41	12
315/80R22.5	18	22	28	9.00	3750	3450	830	830	154	151	M	1076	312	42	12
315/80R22.5	20	22	28	9.00	4000	3350	850	850	156	150	L	1076	312	42	12